

WoodBeQuiet™

Featuring QuietPrint™

acoufelt
making quiet

Acoufelt Wall Plank Product Specifications

Application	For wall and ceiling	
Material	100% Polyester fibers with more than 60% recycled content	
Features	Peel and Stick adhesive	
	METRIC	IMPERIAL
Weight	2400 g/m ² +/- 10%	0.49 lb/ft ² +/- 10%
Plank Size	200mm x 1000mm	8" x 39"
Planks Per Box	15 tiles (3.00m ²)	15 tiles (32.ft ²)
Thickness	12mm +/- 10%	0.47" +/- 10%

Technical specifications

Sound Absorption	AS ISO 354-2006 NRC Value 0.45
Fire Testing	ISO 9705: 1993 Group 1 AS ISO 9705: 2003 Group 1 ASTM E84-17a Class A
Indoor Air Quality	Low VOCs emission, formaldehyde and Phenol-free
Light Fastness	ISO 105-B02 1994, 6-7

For further product information visit acoufelt.com









LEED Leadership in Energy and Environmental Design



Declare.

Installation Method



Specifications are based on average from normal manufacturing tolerances, such variations do not effect product performance. We reserve the right to improve the specification of the product without prior notice. Acoufelt strives to fulfil the needs of their customers by producing the highest quality felt products. However due to the fine, fibrous and textural nature of the product, slight visual imperfections may be seen when viewing the product from less than 1 to 1.5 meters. These slight visual imperfections however, are within normal industry manufacturing tolerances. When installing QuietPrint, we recommend that you align the panels to their closest match at eye level, and allow for +/- 5mm Alignment Tolerance.